



- ① ROUNDED WHITE RIVER ROCK COBBLES 4" MIN. THICKNESS TO 18" MAX WIDTH, WITH ROCK UNIFORMITY. COMPACTED AND FILLED WITH DRY-PACK MORTAR JOINTS.
- ② 5/8" MIN. TO 2-1/2" MAX. JOINT WIDTH. ROCK TO BE EXPOSED 3/4" MIN. TO 1-1/2" MAX. ABOVE SURFACE OF JOINT NOT TO FALL BELOW TOP ELEVATION OF CURB.
- ③ 4" SAND SETTING BASE. COMPACT TO 95%
- ④ INSTALL TYPE "A" CURB PER CITY STD DWG NO 200 AND AS DIRECTED BY THE ENGINEER.
- ⑤ COMPACT SUBGRADE TO 95% STANDARD PROCTOR DENSITY.
- ⑥ THE HEIGHT ABOVE CURB FACE FOR MEDIAN WIDTHS OF 2'-4' IS 4" MAX, FOR MEDIAN WIDTHS 4'-6' IS 6" MAX, MEDIAN WIDTHS 6'-8' IS 8" MAX.
- ⑦ CONTRACTOR SHALL CONSTRUCT A 6' X 6' SAMPLE SECTION FOR FIELD ENGINEER'S APPROVAL.

MORTAR NOTES:

20% BY VOLUME CEMENT (2000 PSI PORTLAND CEMENT), MIN. 80 % BY VOLUME SHARP MASONRY.

CITY OF SAN BERNARDINO / PUBLIC WORKS DEPT.

GROUTED RIVER ROCK MEDIANS

APPROVED 7-21-03

Michael Grubbs
 DIRECTOR OF PUBLIC WORKS/CITY ENGINEER
 CITY ENGINEER

STANDARD
 NO.

206